


Lumped Lowpass Filter

Features/Benefits

- GPO Connectors
- Made in U.S.A.




Parameter	Specification
Cutoff Frequency (Fc)	10000 MHz
Passband	-3 dBa max from 6000 MHz to 10000 MHz
VSWR	1.5 max from 6000 MHz to 10000 MHz
Rejection	-25 dBa min from 11950 MHz to 20000MHz
Temperature, Operating	0°C to +50°C
Temperature, Storage	0°C to +50°C
Mechanical Dimensions	2.000 x 0.400 x 0.300 inches [50.80 x 10.16 x 7.62 mm] (L X W X H)



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES.
TOLERANCES ARE:


INCHES	MILLIMETERS
.XX ± .02	[X.X] ± .5
.XXX ± .010	[X.XX] ± .25
.XXXX ± .0020	[X.XXX] ± .051

This document contains proprietary information and is to be used only for the purposes for which it has been supplied and is not to be duplicated or disclosed in whole or in part without written permission from a duly authorized representative of Knowles.



FREQUENCY (MHZ)	VALUE	SPEC	COMMENTS
6000 - 10000	-1.08 dbA	-3 dbA MAX	
FREQUENCY (MHZ)	VALUE	SPEC	COMMENTS
6000 - 10000	-16.5	1.5 :1 MAX	(S11) - VSWR
6000 - 10000	-14.9	1.5 :1 MAX	(S22) - VSWR

This document contains proprietary information and is to be used only for the purposes for which it has been supplied and is not to be duplicated or disclosed in whole or in part without written permission from a duly authorized representative of Knowles.



FREQUENCY (MHZ)	VALUE	SPEC	COMMENTS
11950 - 20000	-47.1 dbA	-25 dbA MIN	

This document contains proprietary information and is to be used only for the purposes for which it has been supplied and is not to be duplicated or disclosed in whole or in part without written permission from a duly authorized representative of Knowles.