

## 2-18GHz 2-way Wilkinson Power Divider

**PDW06933**

COMPEX • DLI • JOHANSON MFG  
NOVACAP • SYFER • VOLTRONICS  
[www.knowlescapacitors.com](http://www.knowlescapacitors.com)

### DESCRIPTION

DLI's 2-18GHz 2-way power divider / combiner offers unmatched size and performance. This power divider utilizes DLI's low loss temperature stable materials which offer small size and minimal performance variation over temperature.

### FEATURES


- Small Size
- Frequency Stable over Temperature
- Epoxy Mount Wirebondable Package
- Excellent Repeatability
- Moisture Sensitivity Level: MSL1
- Operating & Storage Temp: -55°C to +125°C
- Characteristic Impedance: 50Ω

### SPECIFICATIONS\*

Parameter	Frequency Range (GHz)	Min	Typ.	Max
Nominal Power Splitting (dB)	2-18		3.0	
Nominal Phase Shift (Deg)			0.0	
Amplitude Balance (dB)				± .25
Phase Balance (Deg)				± 5.0
Excess Insertion Loss (dB)				2.5
Return Loss (dB)		14	18	
Isolation (dB)			20	
Input Power (W) <sup>1</sup>				5

\*Electrical specifications based on typical probed performance at room temperature. Insertion loss shall vary ±0.5dB over temperature.

### Typical Measured Performance




## 2-18GHz 2-way Wilkinson Power Divider

**PDW06933**

COMPEX • DLI • JOHANSON MFG  
NOVACAP • SYFER • VOLTRONICS  
[www.knowlescapacitors.com](http://www.knowlescapacitors.com)

### Physical Dimensions



### Recommended PCB Layout

