

## 2 –10 GHz 3-way Power Divider

### PDW11594

[www.knowlesc capacitors.com](http://www.knowlesc capacitors.com)

#### DESCRIPTION

DLI's 2 –10 GHz 3-way power divider / combiner offers unmatched size and performance in a surface mount configuration. This power divider utilizes DLI's low loss temperature stable materials which offer small size and minimal performance variation over temperature.

#### FEATURES

- Small Size
- Frequency Stable over Temperature
- Solder Surface Mount Package
- Excellent Repeatability
- Moisture Sensitivity Level: MSL1
- Operating & Storage Temp: -55°C to +125°C
- Characteristic Impedance: 50Ω

#### Packaging and Ordering Information:

To request tape and reel packaging, please order part number PDW11594-T



#### SPECIFICATIONS\*

Parameter	Frequency Range (GHz)	Min	Typ.	Max
Nominal Power Splitting (dB)	2 - 10		5.5	6.5
Nominal Phase Shift (Deg)			0.0	
Return Loss (dB)		10	14	
Amplitude Balance (dB)				± 0.75
Phase Balance (Deg)			± 6.0	
Isolation (dB)		15	20	
Max CW Input Power** as Divider (W)				6
Max CW Input Power** as Combiner (W)				1.8 ***
Size (L x W x H)	0.470 x 0.210 x 0.020 in. 11.94 x 5.34 x 0.508 mm			

\*Electrical specifications based on typical mounted performance at room temperature. Insertion loss shall vary ±0.5dB over temperature.

\*\*Power rating assumes the component will be mounted to a PCB with good thermally conducting ground via's as outlined in the recommended PCB layout that are connected to an adequate heat sink. Max power is based on 85°C base temperature.

\*\*\*Power rating as a combiner assumes that the incoming signals are of equal amplitude and phase.

Information in this document is for informational and guideline purposes only. All information regarding the Product described in this datasheet is subject to change from time to time at Knowles Precision Devices' sole discretion. It is the customer's sole responsibility to evaluate the suitability of the Product in the customer's particular application. Knowles Precision Devices assumes no responsibility or liability for the use of the information contained within.


2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710

To Order Contact [KCCSales@knowles.com](mailto:KCCSales@knowles.com) | For Technical Inquiries Contact [DLIengineering@knowles.com](mailto:DLIengineering@knowles.com)

## 2 –10 GHz 3-way Power Divider **PDW11594**

[www.knowlescapacitors.com](http://www.knowlescapacitors.com)

### Typical Measured Performance



\*Typical de-embedded measured performance mounted on a connectorized test fixture. DEB is 0.010 in. RO4350B with 50.0Ohm CPW ground traces going into the ports at room temperature.

2777 Route 20 East, Cazenovia, NY 13035 | Ph.: (315)655-8710


To Order Contact [KCCSales@knowles.com](mailto:KCCSales@knowles.com) | For Technical Inquiries Contact [DLIengineering@knowles.com](mailto:DLIengineering@knowles.com)

## 2 –10 GHz 3-way Power Divider PDW11594

[www.knowlescapacitors.com](http://www.knowlescapacitors.com)

### Physical Dimensions

Units = Inches



### Notes :

- Termination Finish:  
ENIG: 3 - 6  $\mu$ inch Au over 50  $\mu$ inch Ni
- Maximum Assembly Process Temperature: 250°C

### Tolerances:

2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710


To Order Contact [KCCSales@knowles.com](mailto:KCCSales@knowles.com) | For Technical Inquiries Contact [DLIengineering@knowles.com](mailto:DLIengineering@knowles.com)

## 2 –10 GHz 3-way Power Divider PDW11594

[www.knowlescapacitors.com](http://www.knowlescapacitors.com)

### Recommended PCB Layout

Units = Inches




### PCB RECOMMENDED STACKUP

Filter is matched to RF layer stackup seen below

Dimensions are specified below in inches ( not to scale)

Board material : RO4350b  
Board material design dk : 3.66  
CPWG : 20mil trace width, 15mil gaps



#### Note :

- 50Ω trace dimensions are application specific.
- Ensure adequate grounding beneath the part.

For further details and best practices, reference the **Microwave Products Guide**, available at: <https://www.knowlescapacitors.com/Support/Catalogs>

2777 Route 20 East, Cazenovia, NY 13035| Ph.: (315)655-8710

To Order Contact [KCCSales@knowles.com](mailto:KCCSales@knowles.com) | For Technical Inquiries Contact [DLIengineering@knowles.com](mailto:DLIengineering@knowles.com)